


Con-Evator PGT

Automatic Vacuum Conveying of Free-Flowing Plastic Granules



Con-Evator PGT



Type	A	B	C1	C2	D1	D2	E	F	G	H1	H2	I1	I2	J1	J2
PGT 4	315	268	583	765	410	490	305	178	270	120	125	150	160	175	170
PGT 6.1	425	310	735	925	455	550	350	178	330	120	125	150	160	175	170
PGT 9	468	359	820	1035	515	680	410	178	380	120	125	150	160	175	170

Technical Data	PGT 4	PGT 6.1	PGT 9
Power supply	3 x 380-480 V 50/60 Hz		
Control Voltage AC	24		
Motor power kW (50/60 Hz)	0.37/0.45	1.1/1.3	1.5/1.75
Installed power kW	0.47/0.54	1.2/1.47	1.60/1.85
Motor r.p.m. min.	2820/3410	2850/3450	2860/3460
Air volume	-	-	170/190
Water column mm	1500/1700	1800/2100	2400/2570
Noise level, dBA	62	68	62
Vacuum hopper, capacity/l	8	16	30
Conveying hose, inner Ø mm	32	38	38
Conveying hose, length, m	3	3	4
Connection cable, m	3	3	3
Telescopic suction probe			
Outer pipe, length, mm	700		
Outer pipe, outer Ø, mm	51	57	57
Inner pipe, length, mm	840		
Inner pipe, Ø, mm	32	38	38
Shipping weight, kg	34	44	64

- Built in control for proportioning valve
- Separate control (option)
- Automatic level control
- 3-phase motor
- Available in 3 sizes: 8, 16 & 30 litre
- Low level alarm
- Automatic filter cleaning by blower reversing
- Low noise level
- Solid aluminum construction
- Blower with capacities ranging from 0.4 to 1.5 kW
- Easy installation
- 3 years warranty, excl. wear parts



Labotek A/S

Stroebjergvej 29, DK-3600 Frederikssund
 Tel +45 4821 8411 | Fax +45 4821 8000
 info@labotek.dk | www.labotek.com